

# AVC761AS



## MPEG4 DVR (4CH)

### FEATURES

#### MPEG4 Technology

- ❖ Local MPEG4 compression format providing crystal clear images with real time performance
- ❖ Remote MPEG4 web transmitting for faster transmission and clearer images via network

#### Multiplex

- ❖ Allows live display, record, playback, backup and network operation at the same time.

#### Backup Function:

- ❖ Supports USB flash drive backup, and network remote recording & backup

#### Remote Surveillance:

- ❖ Remote surveillance with the licensed software AP, IE browser and Mozilla Firefox browser
- ❖ Web surveillance with 20 users simultaneously

#### Intelligent Motion Trigger Recording:

- ❖ With advanced settings for motion detection, scheduled motion detection recording (4 different adjustable factors for the motion detection sensitivity) and convenient search function, customized security environment is achieved.
- ❖ Alarm triggered recording will send alerts with images to the designated e-mails and FTP address
- ❖ Supports pre-alarm recording (8MB)

#### Covert Recording:

- ❖ Blank screen replaces live displays to achieve covert recording


#### A/V Support:

- ❖ Supports 1 audio-in, 1 audio-out to record sounds
- ❖ Supports VGA converter (optional)

#### General:

- ❖ Supports SATA HDD
- ❖ Supports multi-language OSD
- ❖ Supports IR remote control
- ❖ System auto recovery after power failure
- ❖ Supports daylight-saving function
- ❖ Supports manual / timer / motion / alarm / remote recording functions
- ❖ Ensures the authentication of recorded images with the watermark function
- ❖ Supports TCP/IP, PPPoE, DHCP and DDNS network connection

## REAR PANEL



## SPECIFICATIONS

	<b>AVC761AS</b>
Video System	NTSC / PAL (auto detection)
Video Compression Format	MPEG4
Video Input	4 Channels. Composite video signal 1 Vp-p 75Ω BNC
Video Loop Out	4 Channels. Composite video signal 1 Vp-p 75Ω BNC
Video Output	Main Monitor Output: Composite video signal 1 Vp-p 75Ω BNC Call Monitor Output: Composite video signal 1 Vp-p 75Ω BNC
Maximum Recording Rate	Frame: 720×480 pixels with 30 IPS <NTSC> / 720×576 pixels with 25 IPS <PAL> CIF: 352×240 pixels with 120 IPS <NTSC> / 352×288 pixels with 100 IPS <PAL>
Adjustable Recording Speed	Frame: 30, 15, 7, 3 IPS <NTSC> / 25, 12, 6, 3 IPS <PAL> CIF: 120, 60, 30, 15 IPS <NTSC> / 100, 50, 25, 12 IPS <PAL>
Image Quality Setting	Best, High, Normal and Basic
Hard Disk Storage	Support SATA HDD * 1, support HDD capacity over 1000GB
HDD Quick Cleaning	Quick clean up the "index system" of the recorded files. 1000GB under 2 seconds
Recording Mode	Manual / Timer / Motion / Alarm / Remote
Refresh Rate	120 IPS for NTSC / 100 IPS for PAL
Audio I/O	1 audio input, 1 audio output (Mono)
Motion Detection Area	16 × 12 grids per camera for all channels
Motion Detect Sensitivity	4 adjustable variables with precise calculation for motion detection
Pre-alarm Recording	Yes (8MB)
Backup Device	Network / USB Flash Drive
Web Transmitting / Compression Format	MPEG4
Ethernet	10/100 Base-T. Support remote control and live view via Ethernet.
Web Interface	Support licensed software AP, IE browser and Mozilla Firefox browser
Remote Alarm Notification	E-mail images, and upload images to FTP site's specific account
Network Connection	Support TCP/IP, PPPoE, DHCP and DDNS function
PTZ control	Support PELCO-D protocol
IR Transmitter	YES
Dwell Time (Sequential Channel Switch)	Programmable with adjustable dwell time
Alarm I/O	4 inputs, 1 output
Digital Zoom	2X digital zoom (live mode)
Key Lock	Yes
Video Loss Detection	Yes
Camera Title	Support up to 6 letters
Video Adjustable	Hue / Color / Contrast / Brightness
Date Display Format	YY/MM/DD, DD/MM/YY, MM/DD/YY, and Off
Power Source	DC 19V
Power Consumption	< 42 W
Operating Temperature	10°C ~ 40°C (50°F~104°F)
Dimensions (mm)	345(W) x 68.3(H) x 225(D)
System Recovery	System auto recovery after power failure
Optional Peripherals	Keyboard Controller / VGA Converter