

# High Resolutions Dome Camera With OSD



**HC-DS70M**

## Features

- o 1/3"SONY EX-VIEW Effio CCD(960H)
- o 700TVL High Resolution Camera
- o 0.001lux@F1.2
- o High Res 3.6mm lens
- o OSD,HLC, DWDR,Motion Detecions, Privacy Masking 2DNR
- o AGC,AWB and BLC



Model	HC-DS70M
Pick-up device	1/3"SONY EX-VIEW Effio CCD(960H)
Effective pixels	NTSC:976x494,PAL:976x582
Resolution	700 TVL
Min. illumination	Color:0.06lux/F1.2,B/W:0.006Lux/F1.2
Sycn.system	Internal/Line lock
Scan system	2:1 Interlace
S/N ratio	more than 50dB
lens	3.6mm High Res Lens
Electronic shutter	AUTO(1/60(1/50)~1/100,000)/FIXED/MANUAL
DNR	2DNR(Y/C,Y,C,OFF)
BLC	HLC/BLC/OFF
AGC	ON/OFF
DWDR	ON/OFF
Image adjustment	Lightness/Contrast/Sharpness/Tone/Saturation
White balance	MANUAL/USER1/USER2/PUSH LOCK/CRR/ATW
Day&Night	Auto/B/W/Color
Gamma	0.45(default)
Other	7 kinds of language ,Vandal proof, Lightning proof, IP66, 3D bracket adjustable
Video output	1.0Vp-p Composite Video Output, 75 Ohm
Power supply	DC12V±10%
Power consumption	200mA/DC12V
Operating temp	-20°C ~ 50°C