

CP-DY60M-E

High Resolution Dome Camera with OSD



Main Features

- 1/3" Sony CCD
- 600 TVL High Resolution Camera
- 0.05 lux @ F1.2
- 3.6 mm Fixed Lens
- AGC, AES, BLC, Mirror, Privacy Masking and Motion Detection
- CE, FCC and RoHS Certified



Specifications

Image Sensor	1/3" Sony CCD
Pixels	PAL:752Hx582V, NTSC:768Hx494V
Resolution	600 TVL
Min. Illumination	0.05 lux @F1.2
S/N Ratio	more than 48dB
Electronic Shutter	1/50(1/60) - 1/100000 Sec
Flickerless Mode	ON/OFF
Lens	3.6 mm
Gamma	0.45
White Balance (AWB)	Auto
Gain Control (AGC)	ON/OFF Selectable
Back Light Compensation	ON/OFF Selectable
Sync	Internal
Video Output	1.0 Vp-p/75 ohm
Special Functions	OSD, Camera ID, Camera Title, Mirror, Privacy Masking=7, Motion Detection=4
Power Supply	DC 12V ± 5%
Power Consumption	<4W
Dimensions	100 x 65
Weight	400 gms
Operating Temperature	-10~50 °C
Certifications	CE, FCC, RoHS