



## PAN / TILT IP CAMERA



Model.: H 613A  
 Model.: H6 - 186B (With IR Cut Filter & MMC Slot)

### SPECIFICATIONS

Features	System security	Supports three-level account, password, user multi-level authority management
	DDNS (free)	Built in free DDNS system, like http://demo.easyn.hk, 'demo' is serial code
	IE multi-channel view client (free)	No need to install software, support multi-channel monitor & management & check alarm picture via IE
	Super client	1,4,9,16,25,36, 64-channel, no user limited, centralized monitor, remote record and playback, Skype message alarm, skype telephone alarm, meeage alarm etc.
	Superiority	Support multi-channel monitor via cellphone or computer, certified by Microsoft activeX, support most of intelligent phone (such as Iphone, Android, Symbian)
	CPU	Operation system
Microcomputer processor		32Bit RSIC Embedded Processor
Compression format		Motion-JPEG-N
Video	Signal system	CMOS 300,000 pixel
	Frame rate	25fps
	Shutter speed	1/50s-1/100,000s
	Resolution	VGA(640*480), QVGA(320*240)
	Image adjustment	Brightness, contrast, saturation.
	WB, BLC	Auto
Nightvision	Lens	Standard: 3.6mm
	Nightvision	10Φ5 LED lights IR distance: 10m
	Compression format	ADPCM
Audio	Input	Built-in Mircophone
	Output	one channel linear output
	Audio gain	AGC
P/T	Motor	Built-in motor control
	Rotation angle	Horizontal: 270° vertical: 90°
	Rotation speed	11 level pan/tilt rotation speed optional, speed range 15-70°/second
Network	Network interface	RJ-45 10/100Mb self-adaptable Ethernet slot
	Protocol	Support TCP/IP, HTTP, ICMP, DHCP, FTP, SMTP, PPPoE etc.
	Wireless	WIFI, 802.11 b/g
	Online visitor	Support 4 visitors at the same time
Others	IP mode	Dynamic IP address, static IP address, PPPOE
	Shape	Cartoon robot
	Use environment	Indoor use
	Power	DC5V 2A
	Temperature	-10~50 °C
	Humidity	95% RH
	Size	Item size: 111*100*127mm (L*W*H) Package size: 170*170*170mm, L*W*H
Weight	G.W.: 895g, Note: for real products,	
Alarm	Attachment	Power adapter, CD, manual, screws, warranty card
	Input / output	1/1
	Alarm detection	Built-in motion detection, sensitivity can be set
System	Alarm action	Support Email photo, FTP photo upload, preset positions call, GPIO etc.
	System requirement	Microsoft Win98 SE/ME/2000/XP/Vista/Win 7, Internet Explorer 8.0, FireFox, Google Browser
Certification	Certificate	FCC CE SASO RoHS