



SPECTRA

Your Identity Solution Partner



Biometric Reader

www.spectra-vision.com

Affordable BIOMETRIC SECURITY

FingerXs • *INSTAID* • ezCANTEEN • BioSTAMP • PAYPOINT

<http://www.asi.ind.in>



SPECTRA

Your Identity Solution Partner

BioStamp

Biometric Reader

Features

- ⊗ Affordable solution for biometric access security
- ⊗ Most accurate and reliable fingerprint scanner
- ⊗ Elegant design with compact dimensions, suitable for installations on a door frame
- ⊗ Industry standard Weigand interface for easy interface to any access controller

Template Manager

- ⊗ BioStamp comes with fingerprint database management software for easy enrollment and transfer of templates
- ⊗ Auto scan of all the units connected over network
- ⊗ Uses MS Access database to store the centralized information of all the registered fingerprints
- ⊗ The software supports both RS485 and RS232 for template transfers
- ⊗ The templates can either be registered on BioStamp directly or through a USB scanner and can later on be transferred to BioStamp unit.
- ⊗ Configuration of various fingerprint sensor parameters like security level, image quality etc
- ⊗ Configure Weigand parameters like no of bits, pulse interval, pulse width etc
- ⊗ API for third party access management software

Accessories



Enrollment
Sensor



RS232 Interface
Converter

Configuration



Specifications

- ⊗ Optical Fingerprint scanner with 500 dpi resolution
- ⊗ Registration Time <1 Sec , 1:1 Match < 1 sec, 1:N match <1 sec for 1000 templates
- ⊗ False Acceptance Rate (FAR) : 0.001%
- ⊗ False Rejection Rate (FRR) : 0.01%
- ⊗ Capacity to store 1900 fingerprint templates (950 users) expandable up to 9000 fingerprint templates
- ⊗ Built in RFID reader for different authentication modes like only Finger , only Card, Card + Finger
- ⊗ Card reader options - HID iClass, Mifare, HID Prox & EM reader
- ⊗ Configurable Weigand output, connects seamlessly to most access controllers
- ⊗ Support of Command cards for easy user management
- ⊗ Multi color LED indication for successful match
- ⊗ Programmable Buzzer & LED control from controller
- ⊗ RS232/RS485 interface for fingerprint registration
- ⊗ Operating voltage 12VDC
- ⊗ Dimensions = 5.3 cm (L) x 15.5 cm (H) x 3.8 cm(D)

mifare



*Specifications are subject to change without any prior notice

<http://www.asi.ind.in>